

## DESOI PowerInject MB

No. 10440

### Description

The compact and powerful membrane pump DESOI PowerInject MB can be used for refilling of voids, creation of horizontal water barriers, masonry stabilisation and crack injection. The working pressure is infinitely variable from 2 – 20 bar. The ready-mixed material is sucked directly out of the mixing container.

### Material to be used

- Injection mortar
- Cement paste
- Cement suspension
- Aqueous solution

### Delivery range

moving device, 2 x suction system, socket wrench AF41, hook wrench 68 – 75 mm, incl. instruction manual,

No. 11402: Quick snap (LP ball valve R ½", 5 m material hose Ø 13 mm with detachable double nipple R ½", pressure gauge unit with manometer 0 – 40 bar, free passage Ø 9 mm, spring protection against buckling),

No. 21232: LP ball valve R ½" (max. 40 bar, mouth piece, detachable double nipple R ½")

### Advantages

- Pressure control infinitely variable
- Exchangeable suction systems
- Big material passages - high flow rate
- Easy operation and cleaning



1. Main switch

2. Pressure gauge unit with manometer

### Technical data

Supply	230 V
Motor power	1.5 kW
Working pressure - infinitely variable	2 – 20 bar
Delivery rate	max. 8 l/min
Grain size	max. 0.3 mm
Weight	55 kg
L x W x H	55 x 55 x 68 cm

### Accessories

	No.
Spare and wear part set DESOI PowerInject MB	10440-EVS
Set of tools DESOI PowerInject MB	10440-WS