

DESOI PowerInject P1

No. 15747

Description

The small, compact, powerful reciprocating pump DESOI PowerInject P1 is made for machine usable injection resin. As the pump is equipped with a pressure gauge unit with membrane and oil filling, the manometer cannot get stuck as there is no direct contact with the injection resin.

Material to be used

- Epoxy resin
- Polyurethane

Delivery range

drive, pressure control with return and pressure gauge unit with manometer 0 – 250 bar, 2 litre material container transparent, incl. instruction manual, No. 16802: HP material hose - steel (Ø 6 mm, 3 m long, union nuts M12x1.5, solvent resistant), No. 16733: HP injection gun (external thread M12x1.5, whip 0.3 m, 0 – 250 bar, mouth piece)

Advantages

- Seals can be retightened manually - long life
- Exact adjustment of pressure
- Easy operation and cleaning



1. Pressure gauge unit with manometer and pressure regulating valve

Technical data

| | |
|--|-----------------|
| Supply | 230 V |
| Motor power | 0.75 kW |
| Working pressure - infinitely variable | 10 – 200 bar |
| Delivery rate | max. 0.4 l/min |
| Weight | 10 kg |
| L x W x H | 36 x 19 x 53 cm |

Accessories

| | No. |
|--|-----------|
| Spare and wear part set DESOI PowerInject P1 | 15735-EVS |
| Set of tools DESOI PowerInject P1 | 15735-WS |