

DESOI AirPower L36-2C VA

Stainless Steel

No. 17607

Description

The reciprocating pump DESOI AirPower L36-2C VA achieves a delivery of max. 20 l/min at a mixing ratio of 1 : 1. Due to the big valves and pistons also highly viscous material can be used without any problems. The result is a very maintenance-friendly machine including suitable accessories.

Material to be used

- 2 component injection resin

Delivery range

moving device with wheel set, suction system, 2x manometer 0 – 400 bar, incl. instruction manual,
No. 16875: HP material hose - stainless steel (Ø 10 mm, 10 m long, union nuts G 3/8", solvent resistant, component B),
No. 16876: HP material hose - stainless steel (Ø 10 mm, 10 m long, union nuts G 1/2", solvent resistant, component A),
No. 17815-12: 2C mixing head - stainless steel (2 x HP ball valve, 2 x check valve, mixing tube with 12 x inline static mixer, whip 0.3 m long, sliding coupling straight with free passage Ø 2.5 mm, material hose connections: component A: G 1/2"; component B: G 3/8")

Advantages

- Manometers at machine outlet for pressure control of each components
- Big material passage - suitable also for highly viscous material
- Adjustment of the material volume
- Can be equipped with DESOI Flow Control (electronic recording system)



16875, 16876



17815-12



1. Pressure regulator with manometer and anti-freeze device
2. Manometer combination

Technical data

Working pressure - infinitely variable	5 – 200 bar
Delivery rate	max. 20 l/min
Air consumption	2.5 m ³ /min
Transmission ratio	1 : 25
Mixing ratio	1 : 1
Air pressure	max. 8 bar
Weight	92 kg
L x W x H	110 x 55 x 65 cm

Accessories

	No.
Spare and wear part set DESOI AirPower L36-2C VA	17607-EVS
Set of tools DESOI AirPower L36-2C VA	17607-WS